

RACKMOUNT USB + PS/2 KVM DRAWER WITH REAL MOUSE

Provides space-saving convenient control with a real mouse



RACKMUX-V17-MP

Features & Applications

The RACKMUX® USB + PS/2 KVM Drawer with Real Mouse combines an LCD monitor, keyboard, and real mouse with mouse pocket. This KVM drawer is ideal for anyone who prefers using a real mouse to touchpads or trackballs. The low, 1RU (44mm) profile saves space in crammed server racks. Connect this compact data entry device to a KVM switch for convenient control of all attached computers.

- Allows users to store and use a real mouse.
- 17" TFT panel active matrix LCD display monitor.
- Compatible with USB and PS/2 computers.
- Torque-friction hinges—monitor does not wobble, spring, or slam shut.
- Features smooth-action ball bearing rackmount slides.
- Drawer locks into place when open to prevent it from sliding in and out of the rack.
- Rugged steel construction with durable powder coat finish.
- LCD auto-shutoff in the closed position.
- Internal cable arm provides proper cable management for sliding the drawer open and closed.
- Equipped with On Screen Display (OSD).

Specifications

Host Interface

- Compatible with PS/2, UNIX and USB-enabled computers.
- Multiplatform support: Windows 2000/XP/Vista/Server 2000/2003/2008, Solaris, Linux, FreeBSD, and MAC OS 9/10.
- One female 15-pin HD, one female USB Type B, and two female 6-pin miniDIN connectors.
- Use with NTI Multi-Platform KVM Switches to control multiple PC, SUN and MAC computers.
- 1.5m attached cables with one male 15-pin HD, two male 6-pin miniDIN, and two male USB Type A connectors for connecting to host.

Monitor

- Backward-folding 17" TFT/LCD monitor.
- 1280x1024 video resolution.
- OSD controls for brightness, contrast, phase, pitch, Horiz- and Vert-center alignment, zoom and color adjustment.
- Frequency:
 - Horizontal: 31.5 to 80 kHz.
 - Vertical: 60 to 85 Hz.
- Viewing angle:
 - Horizontal: 178°, Vertical: 178°
- Sync: H/V Separate (TTL).
- 300 nits brightness and 500:1 contrast ratio typical.
- Supports DDC1 and DDC2B protocols.

Devices

- Compact, full-function UK-layout keyboard with 84-key Windows layout.
- Three-button optical mouse included.

Dimensions

- WxDxH (mm): 483x754.4x44
- Weight: 14.8 kg.
- Drawer is adjustable to various rack depths from 754.4mm deep to 1092.2mm deep.

Power

- 110 to 220 VAC at 50 or 60 Hz via AC adapter.

Environmental

- Operating temperature: 0°C to 40°C (32°F to 104°F).
- Storage temperature: -20°C to 60°C (-4°F to 140°F).
- Operating and Storage Relative Humidity: 20 to 90% non-condensing RH.

Regulatory Approvals

- CE, RoHS

Warranty

- Two years

